
TX500-1800B



High volume belt-fed textile printer







High quality belt-fed printer for volume production of textiles ...

Mimaki

Featuring an automated, belt-fed conveyance system, the Mimaki TX500-1800B is able to print direct to a broad range of natural and man-made

fabrics, with a unique combination of both high quality and high production speeds. Capable of delivering long print runs for the fashion and soft furnishing markets, TX500-1800B offers the perfect digital textile manufacturing solution.

ENGINEERING EXCELLENCE AND CREATIVE INNOVATION

Founded in Japan in 1975, Mimaki Engineering has steadily grown by reputation and influence into a global company with large operational bases in Asia and the Pacific. United States and Europe.


Renowned for award-winning performance, peerless build quality and innovative technology, Mimaki has established itself as a leading manufacturer of wide-format inkjet printers and cutting machines for the sign and graphics, textile and apparel and industrial markets. In addition, Mimaki also provides a comprehensive range of supporting products; hardware, software and associated consumable items, such as inks and cutting blades.

From outdoor signage and billboards to interior decoration and furnishing, from packaging and labels to promotional gifts and apparel, Mimaki is committed to developing technology that sets new industry standards, producing machines and products that turn the imagination of our customers into breath-taking reality.

... Mimaki delivers

TX500-1800B delivers...

- High speed production up to 140 m²/h (in high-speed mode)
- Automated belt-fed conveyance system
- Multiple ink types to print to; Cotton, Polyester, Hemp (Linen) and Rayon
- Mimaki Advanced Pass System (MAPS) & Correct Feeding Control CFC) reducing imperfections in high production mode
- Mimaki Degassing Module (MDM-20) enabling use of bottled inks
- Mist Removal Filter for enhanced print stability
- Media roll handling up to 400 mm diameter and maximum weight of 60 kg




TX500-1800B



Create ... Fashion and Apparel, including scarves, dresses, shirts, upholstery, bedding and soft furnishing fabrics, Exhibition Graphics, Wall Art, Textile PoS and much more...

KEY TECHNICAL FEATURES ...

Up to 140 m²/h print speed TX500-1800B features newly developed 6 print head technology, in staggered formation, featuring 1280 nozzles per printhead, delivering up to 140 m²/h in 4-colour high speed mode. Variable drop sizes of 7 picolitres and 21 picolitres are available. | Up to 140 m²/h in 4-colour high speed mode. Variable drop sizes of 7 picolitres and 21 picolitres are available. | Up to 140 m²/h in 4-colour high speed mode. Variable drop sizes of 7 picolitres and 21 picolitres are available. | Up to 140 m²/h in 4-colour high speed mode. Variable drop sizes of 7 picolitres and 21 picolitres are available. | Up to 140 m²/h in 4-colour high speed mode. Variable drop sizes of 7 picolitres are available. | Up to 140 m²/h in 4-colour speed mode. Variable drop sizes of 7 picolitres are available. | Up to 140 m²/h in 4-colour speed mode. Variable drop sizes of 7 picolitres are available. | Up to 140 m²/h in 4-colour speed mode. Variable drop sizes of 7 picolitres are available. | Up to 140 m²/h in 4-colour speed mode. Variable drop sizes of 7 picolitres are available. | Up to 140 m²/h in 4-colour speed mode. Variable drop sizes of 7 picolitres are available. | Up to 140 m²/h in 4-colour speed mode. Variable drop sizes of 7 picolitres are available. | Up to 140 m²/h in 4-colour speed mode. Variable drop sizes of 7 picolitres are available. | Up to 140 m²/h in 4-colour speed mode. Variable drop sizes of 7 picolitres are available. | Up to 140 m²/h in 4-colour speed mode. Variable drop sizes of 7 picolitres are available. | Up to 140 m²/h in 4-colour speed mode. Variable drop sizes of 7 picolitres are available. | Up to 140 m²/h in 4-colour speed mode. Variable drop sizes of 7 picolitres are available. | Up to 140 m²/h in 4-colour speed mode. Variable drop sizes of 7 picolitres are available.



High quality, reliable print output Correct Feeding Control (CFC) This function reduces and corrects banding issues by measuring the feed rate of the fabric and automatically reducing and correcting the level differences in the joints of the conveyance belt. Mimaki Advanced Pass System (MAPS) When banding cannot be eliminated by feed correction, the MAPS function makes it less visible by dispersing pass boundaries. (NB: when using MAPS, the print speed depends on the selected mode)

Nozzle Recovery Function


In the event of a nozzle malfunction not being repairable by the use of the maintenance function, printing can continue by the use of another nozzle, without any loss of productivity or reduction in image quality.

User-friendly functions

Uninterrupted Ink Supply System (UISS)

Two ink bottles per colour can be set with the UISS function. When an ink bottle runs out, another bottle of the same colour automatically starts supplying ink.

Mimaki Degassing Module (MDM-20) Equipped with MDM-20 which eliminates gasses and bubbles inside the ink, enabling the printer to use bottled inks instead of conventional degassed ink packs, thereby reducing ink costs.



Sophisticated RIP software maximizes the performance of TX500-1800B

OPTIONAL

User friendly RIP "RasterLink 6" comes as standard aster Link

- More beautiful and advanced print results are achieved by following a user-fri Colour replacement function enhances the ability to re-create printed images.
- Print colour can be simulated on Illustrator / Photoshop without an actual print.
- Program update and profile download can be easily performed via internet

OPTIONAL



Specifications

Item		TX500-1800B		
Print head		On demand piezo head (6 heads in staggered configuration)		
Maximum print width		1,820 mm		
Print resolution		300dpi, 450dpi, 600dpi, 900dpi, 1200dpi		
Print modes		4colour	6/8colour	
	Draft	300x300HQ/2pass/BI	300x300HQ/4pass/BI	
	High Speed	300x450HQ/3pass/BI	300x450HQ/6pass/BI/HI	
	Standard	600x900dpi/6pass/BI/HI	600x600dpi/8pass/BI/HI	
	High Resolution	600x1200dpi/8pass/BI/HI	600x1200dpi/16pass/BI/HI	
Ink	Туре	Sb300 (Sublimation) / RC300 (Reactive)		
	Supply	8 x 2L bottles		
	Degassing module	Equipped with MDM-20		
	Colour variation	Sublimation Sb300	Reactive RC300	
Ink	4 colour	•	•	
	6 colour	х	х	
	8 colour	x	•	
	Size	Minimum: 210 mm, Maximum: 1,830 mm		
Media	Thickness	Up to 5 mm		
	Roll weight	Up to 60kg		
	Printing surface	Inside / Outside selectable		
	Roll diameter	Roll diameter: 400 mm, Inside diameter: 76 mm		
Media heater		Optional External drying heater		
Media take-up device		Powered take-up device		
Print gap		1.5 mm ~ 7 mm (user selectable)		
Interface		USB2.0		
Applicable standards		VCCI class A, FCC class A, UL60950-1, RoHS directive CE Marking (EMC, Low voltage and Machinery directive)		
Power specifications		Single-phase AC 380~420 V, 20 A or under		
Power consumption		Less than 10kVA (excludes optional heater)		
Operating environment		Temperature: 20°C-30°C / Humidity: 35-65 % RH (No condensation)		
External dimensions (WxDxH)		3,830 x 2,600 x 1,800 mm (excluding ink supply unit)		
Weight		1,840kg		
Compressed Air Pressure		6-8 Bar / 40 litres / minute		
Water F	Requirement	50 litres / hour		

Options and Supplies

Item No.	Name	Remarks
SB300- * -BB	Sublimation dye ink Sb300 (* Bl/M/Y/KD)	2 litre bottle
RC300- * -BB	Reactive dye ink Rc300 (* C/M/Y/K/Lk/Bl/Or/R)	2 litre bottle
FL003-Z-BB	Washing liquid 03	2 litre bottle for ink replacement
ML003-Z-K1	Washing liquid 03 Maintenance kit	For daily maintenance
SPA-0188	Maintenance kit	20 HF filters, 30 filters for intake/ exhaust fan, Protective goggles, 10 clean sticks
SPA-0189	Head filter replacement kit	20 HF filters
SPA-0193	Wiper rubber replacement kit	2 wipers
SPA-0194	Cap rubber replacement kit	6 cap rubbers
SPA-0211	Supply air filter replacement kit	2 filter elements
SPA-0196	Supply ink filter replacement kit	
SPA-0197	Waste ink tank SL	(Placed in a box)
OPT-J0137	USB2.0 cable (5m)	Connector between PC for Rasterlink 6 and printer unit
SPM-005	MPMII i1ProSet	Colour management software + Colorimeter
SPC-0397	Glue for conveyor belt (1Lt Can)	

Optional heaters to further improve productivity

You can choose between two types of heaters according to your operating conditions.



Some of the samples in this folder are artificial renderings • Specifications, design and dimensions stated in this folder may be subject to change without notice (for technical improvements, etc.)
The corporate and merchandise names written on this folder are the trademark of the respective corporations • Inkjet printers print using extreme fine dots, so colours may vary after replacem
of the printing heads, also note that if using multiple printer units, colours could vary slightly from one unit to other unit due to slight individual differences • Compositor's errors reserved

Mimaki

www.mimakieurope.com info@mimakieurope.com **ず**@ MimakiEurope



Celupal Internacional, S. de R.L. de C.V.

Calle Tres #53, Parque Industrial Naucalpan C.P. 533370, Naucalpan, Edo, de México Tel. (55) 2625-2990/01 800 000 CELU (2358) info@celupal.com

Sucursal Toluca

Calle Emiliano Zapata No. 79 Col. "El Carmen" Totoltepec Municipio de Toluca Estado de Mexico Tel: (722) 283 1039, (722) 283 1042 toluca@celupal.com

Sucursal. Algarín

Sucursal Querétaro

Pról. Corregidora Nte. #1220 Arboledas del Parque Querétaro, Qro. C.P. 76140 Tel: (44) 2340 7722/23, (44) 2340 7080 queretaro@celupal.com

Sucursal Monterrev

Pablo A. González Garza #811 (Fleteros) Col. Mitras Sur, C.P. 64020, Monterrey, N.L. Tel:/Fax: (81) 1936 6074

monterrey@celupal.com

Sucursal Puebla Bodega #133

Antiquo camino a la resurrección #10428 Parque industrial resurrección Puebla, Puebla C.P. 72228 puebla@celupal.com

Mimaki Europe B.V. Stammerdiik 7E. 1112 AA Diemen, The Netherlands Tel: +31 (0)20 4627640 MFUTX500B01-F

Sucursal Guadalajara Matías Romero #1144, Col. San Carlos

C.P. 44460, Guadalajara, Jal. Tel (33) 3619 5046 quadalajara@celupal.com

Sucursal. Mérida

Calle 17 No. 316, Manzana 8 Ciudad Industrial, Mérida, Yucatán Tel: (999) 946 0908

Bolívar # 505 Local B. colonia Algarín Delegación Cuauhtémoc D.F. C.P.06880 Tel: (55)5530 4456 / 5519 2189 merida@celupal.com algarin@celupal.com

Sucursal Chihuahua

Av. Industrias No.6501-12 Col. Nombre de Dios (Entre Zaragoza y Juan Escutia) Chihuahua, Chih. C.P. 31105 01800 000 CELU

chihuahua@celupal.com