

UJF-3042HG

UJF-3042FX
UV PRINTER



UV LED flatbed desktop printer ...



INDUSTRIAL
PRODUCTS



eco

Mimaki

The world imagines... Mimaki delivers



The most versatile UV LED flatbed printer on the market

Providing a unique solution for short runs and on-demand printing the UJF-3042 series offers unrivalled versatility and high quality print reproduction on an almost unbelievable range of materials, products and substrates. With its compact desktop format the UJF-3042 series offers unlimited possibilities to the end user.

UJF-3042 Series delivers ...

- Outstanding print quality and reliability
- Space-saving compact desktop design
- Direct printing on substrates up to 50 mm thick (FX model) and 150 mm (HG model)
- Simultaneous printing of colour and white
- White ink and clear varnish
- Automatic primer application function
- HG Model features additional two print channels for 6-colour printing plus white and clear inks
- Beautiful, seamless 360 degree surface printing on cylindrical items with the Kebab option (HG model)

UV LED CURING
300 x 420 mm MAX. PRINT SIZE
1440 x 1200 dpi MAX. RESOLUTION
MAX. MEDIA THICKNESS 150 mm (HG model)
4 / 6 COLOUR PRINT + WHITE + CLEAR

UJF-3042FX
UV PRINTER

UJF-3042HG



Additional print head + increased print height facilitates wider range of media.

Create ... Promotional gifts, display cards, name badges, control panels, pens, stationery, fridge magnets, key rings, gift boxes, USB sticks, mobile phone and laptop cases, small format signage...

KEY TECHNICAL FEATURES ...

3 types of UV inks

- LH-100 hard UV ink excels in scratch and chemical resistance as well as colour reproduction. (CMYK, W, Cl, Pr)
- LF-200 flexible UV ink enables stretching of ink up to 200% during post-processing work. (CMYK, W)
- LF-140 offers strong gradation in 6-colour printing and is more flexible than LH-100. (CMYK, Lc, Lm, W, Pr)*

* LF-140 ink set does not include clear ink. You can use a combination with LH-100 clear ink.

Simultaneous white ink under and overprint

Print outstandingly colourful, bright images on transparent and coloured substrates with white ink under or overprint without slowing down print speed.



4/6 colours only
Without white ink as a basis for overprinting, the colours are not as vivid as they should be.



4/6 colours + white
With the white ink overlay print, the images are bright and vivid.

< Sample prints on transparent acrylics >

Add value with glossy and layered finishes

Add value to your prints using clear ink to realise glossy finishes and to further protect your image.




Useful functions to ensure print quality

- Mimaki Spray Suppressor System prevents satellite ink drops, ensuring higher print reliability, consistency, and quality.
- Nozzle Recovery Function temporarily restores print quality, reducing potential downtime if maintenance issues should arise.
- Mimaki Circulation Technology (MCT) is a newly developed white ink circulation system that prevents pigment sedimentation and reduces ink waste. Available on UJF-3042HG.


Automatic primer application functionality

Both models incorporate an automatic primer feature. The new inkjet primer cartridges are simply inserted into the corresponding ink slot of UJF-3042, enabling the primer to specifically target the print image area only.

(*) When printing with primer and white or clear ink, production speed is reduced by approximately 50%. Please always test your intended materials before using primer.



Unlimited possibilities



Sophisticated RIP software maximizes the performance of UJF-3042

RasterLink6

Additional useful functions

1. JIG & Template function

Registration of templates is achieved through a 'JIG layout function' parameter in RasterLink6, allowing the designed image to be placed inside the template layout procedure and accurately positioned for print setup and registration of image file.

2. Web update function

Program update and profile download can be easily performed via the internet.

User friendly RIP key features

- Easy to follow icons enable intuitive and user-friendly operation
- Related settings feature in one window to simplify RIP operations, with 'Register as Favourite' option available for regularly used layouts
- Printing progress can be monitored on the main screen

Specifications

Item	Specifications	
Print head	On-demand Piezo head	
Print resolution	720 x 600 dpi, 1440 x 1200 dpi	
Ink	Kind	LH-100 hard UV curable ink (C/M/Y/K/W/CI)
		LF-200 flexible UV curable ink (C/M/Y/K/W)
		LF-140 (C/M/Y/K/Lc/Lm/W)
	Capacity	220 ml cartridge / 600 ml ink pack
Inkjet primer	PR-100 (220 ml cartridge / 600 ml ink pack)	
Maximum print size	Width: 300 mm, Length: 420 mm	
Media	Max. size	Width: 364 mm, Length: 463 mm
	Thickness	(FX) Up to 50 mm / (HG) Up to 150 mm
	Weight	Up to 5 kg
Media set device	Air suction by vacuum	
UV device	UV LED	
Interface	USB 2.0	
Applicable standard	VCCI class A, FCC class A, UL, RoHS Directive, CE Marking	
Power specifications	AC 100 – 240 V (Automated voltage conversion)	
Power consumption	Less than 0.5 kVA	
Operational environment	Temperature	20 – 35°C (68 – 95°F)
	Humidity	35 – 65% Rh
	Dust	Equivalent to normal office level
Dimensions (W x D x H) / Weight	(FX) 1,200 x 1,090 x 770 mm / 113 kg	
	(HG) 1,200 x 966 x 920 mm / 130 kg	

Supplies

Item	Item No.	Remarks
Dedicated UV ink	LH-100	SPC-0659 C/M/Y/K/W/CI 220 ml cartridge
		SPC-0597 C/M/Y/K/W/CI 600 ml ink pack
	LF-200	SPC-0591 C/M/Y/K/W 600 ml ink pack
	LF-140	SPC-0727 C/M/Y/K/Lc/Lm/W 220 ml cartridge
		SPC-0728 C/M/Y/K/Lc/Lm/W 600 ml ink pack
Inkjet primer	PR-100	SPC-0731 220 ml cartridge
		SPC-0732 600 ml ink pack
Eco case	OPT-J0237	8 cases

1. 600 ml ink pack requires eco cartridge (OPT-J0237). Eco cartridges can be used repeatedly by replacing ink packs.
2. Inkjet primer cannot be used in conjunction with LF-200 inks.
3. Clear ink is not available for LF-140 inks. However, LH-100 clear ink can be used in combination with LF-140 inks.

⚠ Inks and substrates

- Please note that properties, adhesion, weather resistance, etc. of ink and substrates can vary. Therefore please test materials before printing.
- Some substrates require primer before printing. Please test materials beforehand or ask your sales representative.

Also available: Kebab Option for Printing on Cylindrical Products

Using rotary rollers, the Kebab option rotates the print object, enabling seamless 360 degree printing on the entire surface of the cylindrical item. This option can take up various materials of different sizes, ranging from 30 - 330mm in length and 10 - 110mm in diameter.

Easy setup. Mount Kebab option on the printer, set the product on the rollers and start automatic 360 degree printing using RasterLink6 software.

Kebab option is available separately and compatible with the UJF-3042HG and UJF-6042.



• Some of the samples in this folder are artificial renderings • Specifications, design and dimensions stated in this folder may be subject to change without notice (for technical improvements, etc.)
 • The corporate and merchandise names written on this folder are the trademark of the respective corporations • Inkjet printers print using extreme fine dots, so colours may vary after replacement of the printing heads, also note that if using multiple printer units, colours could vary slightly from one unit to other unit due to slight individual differences • Compositor's errors reserved

Mimaki®

info@mimakieurope.com
 @MimakiEurope

Celupal

● ● ● DISTRIBUIDOR LÍDER EN PAPELES, PLOTTERS E INSUMOS

<p>Corporativo 01800 000 CELU info@celupal.com</p>	<p>Sucursal Toluca (722) 283 1039 toluca@celupaL.com</p>	<p>Sucursal Querétaro (422) 840 7722, 23 queretaro@celupaL.com</p>	<p>Sucursal Celupal Monterrey (81) 1936 6074 monterrey@celupaL.com</p>	<p>Sucursal Guadalajara (33) 3619 5046 guadalajara@celupaL.com</p>
<p>Sucursal Mérida (999) 946 0908 merida@celupaL.com</p>	<p>Sucursal Algarín (55) 5519 2189 algarin@celupaL.com</p>	<p>Sucursal Chihuahua (614) 417 0071 chihuahua@celupaL.com</p>	<p>Sucursal Puebla (222) 222 9416 puebla@celupaL.com</p>	<p>Sucursal Cancún (998) 206 8489 cancion@celupaL.com</p>