



VVCUT CUTTING PLOTTER VT SERIES



CONTACTO

<p>Corporativo (55) 2625 2990 01800 000 CELU info@celupal.com</p>	<p>Sucursal Toluca (722) 283 1039 (722) 437 6202 toluca@celupal.com</p>	<p>Sucursal Querétaro (422) 340 7722, 23 (422) 340 7080 queretaro@celupal.com</p>	<p>Sucursal Monterrey (81) 1936 6074 monterrey@celupal.com</p>	<p>Sucursal Guadalajara (33) 3619 5046 guadalajara@celupal.com</p>
<p>Sucursal Mérida (999) 946 0908 merida@celupal.com</p>	<p>Sucursal Algarín (55) 5530 4456 (55) 5519 2189 algarin@celupal.com</p>	<p>Sucursal Chihuahua (614) 417 0071 chihuahua@celupal.com</p>	<p>Sucursal Puebla (222) 222 9416 (222) 222 7417 puebla@celupal.com</p>	<p>Sucursal Cancún (998) 206 8489 cancun@celupal.com</p>



VT-59L / VT-48L / VT-24L

Product Basic Parameter

MODEL NUMBER	VT-59L	VT-48L	VT-24L
Material	Sheet metal +aluminum alloy	Sheet metal +aluminum alloy	Sheet metal +aluminum alloy
Max.Paper feed width	1600MM	1300MM	740MM
Cutting Speed	50-800MM/S	50-800MM/S	50-800MM/S
Cutting Precision	0.005MM	0.005MM	0.005MM
Cutting force	5-500g	5-500g	5-500g
Idling Speed	0-3 gear adjustable	0-3 gear adjustable	0-3 gear adjustable
Control System			
Mainboard	32-bit ARM7 CPU,4MB	32-bit ARM7 CPU,4MB	32-bit ARM7 CPU,4MB
Transmission mode	Serial Port+USB+U disk	Serial Port+USB+U disk	Serial Port+USB+U disk
Repeat Function	1 - 500pcs	1 - 500pcs	1 - 500pcs
Plotter Instruction	Compatible DM/PL,HP/GL	Compatible DM/PL,HP/GL	Compatible DM/PL,HP/GL
Cutting Consumable			
Blade	Diameter 1.49mm the tungsten cutter	Diameter 1.49mm the tungsten cutter	Diameter 1.49mm the tungsten cutter
Max.Cutting Size	1500MM	1205MM	635MM
Paper feeding way	Dual paper stick flat manually	Dual paper stick flat manually	Dual paper stick flat manually
Precision			
Cutting thickness	0.05MM-1MM	0.05MM-1MM	0.05MM-1MM
Noise	60-65dB	60-65dB	60-65dB
Control Panel	11 silicon buttons + LCD touch screen	11 silicon buttons + LCD touch screen	11 silicon buttons + LCD touch screen
Repeat Function	Offline a key re-engraved to start	Offline a key re-engraved to start	Offline a key re-engraved to start
Memory Function	Power off doesn't remove source files	Power off doesn't remove source files	Power off doesn't remove source files
Transmission speed	38.4K/56K	38.4K/56K	38.4K/56K
Display	Chinese and English Display Switch	Chinese and English Display Switch	Chinese and English Display Switch
Output software	Artcut,signcut flexi CorelDRAW\CAD\Ai\etc	Artcut,signcut flexi CorelDRAW\CAD\Ai\etc	Artcut,signcut flexi CorelDRAW\CAD\Ai\etc

Applicable Industries

Advertisement; Glass sandblasting; Marble blasting; Die cutting samples; Article giftware making; Car/Wall sticker; Paper Pattern; Printing; Logo and Signs

Note: The above technical parameters are subject to change without any other notice. Vivision Technology Ltd have the final interpretation.